

SOLCEM

Solk lens

Cleaning Solvent for Resin Products

DESCRIPTION

Solk lens is a specially formulated solvent for cleaning resin products from tools and equipment before the resin has hardened, and for removing any residual release agent from formwork.

Colour	Product Code	Size
Colourless	SOLKLENS25	25 litres

FEATURES & BENEFITS

- Tool cleaning product.
- Formwork cleaning product.

APPLICATION

- When removing resin from tools, clean with Solklens immediately after use before the resin has hardened.
- When removing any residual release agent from formwork, the surface should be wiped with a rag soaked in Solklens.
- When complete the surfaces should then be wiped over with a clean dry cloth.
- When using epoxy resin mortars, Solklens should be used to wipe over the float face to assist in obtaining a good smooth finish.

STORAGE

Keep containers sealed. Store in dry conditions at room temperature and away from direct heat. All applicable storage requirements for flammable materials should be observed.

SHELF LIFE

1 year in sealed container.

TECHNICAL DATA

Appearance / Colour	Colourless low viscosity liquid
Density	0.860
Flash Point	25°C
Solubility	Insoluble in water Soluble in Petroleum Ether

HEALTH & SAFETY

Solk lens is flammable with a flash point of 25°C. Do not permit smoking or naked flame and maintain adequate ventilation in the vicinity of the working area.

Avoid skin contact and never use Solklens for cleaning skin as it will have a de-fatting affect. Wearing of overalls, gloves and protective eyewear should be considered, together with the application of a suitable barrier cream to hands.

If contact with eyes should occur, irrigate immediately with copious quantities of clean water and seek medical attention without delay.